



APPROVED LITHIUM (LiPo/LiFe) BATTERY LIST. 2024 v3.2 - 2S ONLY

INTERNATIONAL FEDERATION OF MODEL AUTO RACING

Batteries received by IFMAR for approval, from 2013. NOTE: Batteries shown on lists: 2010 - 2012 are also allowed. IFMAR rules do not limit capacity or power output of batteries. Values below are Manufacturers data. -- Packs factory sealed (glue, weld etc). Battery packs must be able to be disconnected within the Car quickly without the use of tools. Direct soldering is not allowed. It is essential that batteries on this list are charged using a 2S LiPo compatible charger. It is advisable to restrict charge rates to 1C. It is strictly **NOT ALLOWED**, to charge Lithium Batteries to give an output voltage exceeding :- **2S LiPo - 8.40v. 2S LiFe - 7.40v**. Closed LiPo 'Sack' must be used when charging.

2024 IFMAR PRODUCTS LIST -- 2S Stick and 2S Saddle Lithium Batteries. - 06.08.2024



BATTERIES ON THIS HOMOLOGATION LIST HAVE BEEN CERTIFIED FOR COMPLIANCE WITH UN38.3, TESTS T1-T8.

Submitted By:	Label Details: Part Number	Illustration Only:	Manufacturer Supplied Data:	IFMAR Measured Specificaitons:	Approval Date:
---------------	-------------------------------	--------------------	--------------------------------	-----------------------------------	----------------

BATTERIES BELOW THIS LEVEL ARE APPROVED BY IFMAR FOR 2024 WORLD CHAMPIONSHIP EVENTS.

2S LiPo STICK BATTERIES

Associated Electronics	REEDY Zappers 8200mah - 7.6v #27379		5mm Bullets - 63wh	137.95mm x 47mm x 24.95mm - Weight 325g-335g	10.07.2024
EZ Power	EZ Power 4400mah - 7.6v EZP4400		5mm Bullets - 33.44wh	95.65mm x 46.70mm x 19.85mm Weight 160g-170g	10.07.2024
Fido	Fido 6300HV - 7.6V. Fi63130-2S2PHV		5mm Bullets - 47.88wh	96.4mm x 47mm x 25mm- Weight 220g-230g	10.07.2024
Fido	Fido 5000HV - 7.6V. Fi50135-2S1P		5mm Bullets - 38wh	96.10mm x 47mm x 20.65mm- Weight 175g-185g	10.07.2024
Fido	Fido 4500HV - 7.6V. Fi45130-2S1PHV		5mm Bullets - 34.2wh	96.10mm x 47mm x 20.65mm- Weight 155g-165g	10.07.2024
Fido	Fido 8200 - 7.4V. Fi82130-2S2P		5mm Bullets - 60.7wh	138.25mm x 46.75mm x 25mm - Weight 315g-325g	10.07.2024
Fido	Fido 5900 - 7.4V. Fi59130-2S1P		5mm Bullets - 43.7wh	139mm x 47mm x 19.90mm - Weight 235g-245g	10.07.2024
Fido	Fido 6500 - 7.4V. Fi65220-2S2P		5mm Bullets - 48.1wh	139mm x 46.90mm x 23.10mm - Weight 280g-290g	10.07.2024
Fido	Fido 10000HV - 7.6V. Fi100130-2S2P		5mm Bullets - 76wh	138.5mm x 46.65mm x 25mm - Weight 305g-315g	10.07.2024
GENSACE	REDLINE 5100 - GEA51002S14M5		5mm Bullets - 38.76wh	112.25mm X 47mm X 19.25mm- Weight 185g-195g	10.07.2024

GENSACE	REDLINE 6600 - GEA66002S14D5		5mm Bullets - 50.16wh	138.25mm X 46.35mm X 20.10mm - Weight 240g-250g	10.07.2024
GENSACE	REDLINE 6500 - GEA65002S14S5		5mm Bullets - 49.40wh	96mm X 46.85mm X 25mm - Weight 225g-235g	10.07.2024
GENSACE	REDLINE 5000 - GEA50002S14S5		5mm Bullets - 38wh	96.35mm X 46.80mm X 20.75mm - Weight 175g-185g	10.07.2024
GENSACE	REDLINE 4400 - GEA44002S14S5		5mm Bullets - 33.44wh	96.5mm X 47mm X 19mm - Weight 160g-170g	10.07.2024
GENSACE	REDLINE 6100 - GEA61002S14D5		5mm Bullets - 46.36wh	138.95mm X 46.85mm X 18.20mm - Weight 225g-235g	10.07.2024
GENSACE	REDLINE 6500 - GEA65002S14D5		5mm Bullets - 49.4wh	139mm X 47mm X 22.25mm - Weight 260g-270g	10.07.2024
GENSACE	REDLIEN 8500 - GEA85002S14D5		5mm Bullets - 84.4wh	139mm X 46.70mm X 25.1mm- Weight 305g-315g	10.07.2024
GENSACE	REDLINE 6000 - GEA60002S14D5		5mm Bullets - 45.6wh	96.25mm X 46.75mm X 24.75mm - Weight 220g-230g	10.07.2024
GENSACE	REDLINE 5300 - GEA53002S14D5		5mm Bullets - 40.28wh	96mm X 46.80mm X 22.95mm- Weight 198g-208g	10.07.2024
GENSACE	REDLINE 4200 - GEA42002S14D5		5mm Bullets - 31.92wh	96mm X 47mm X 19mm - Weight 158g-168g	10.07.2024
R1	R1 6500 - R1- 030048		5mm Bullets - 48.1wh	138.95mm X 47.2mm X 22.50mm- Weight 280g-290g	10.07.2024
R1	R1 5900 - R1- 030037		5mm Bullets - 44.64wh	138.65mm X 46.85mm X 19.5mm - Weight 236g-246g	10.07.2024
R1	R1 8400 - R1- 03009-S		5mm Bullets - 64wh	138mm X 47mm X 25mm - Weight 328g-338g	10.07.2024
R1	R1 7000 - R1- 030051		5mm Bullets - 53wh	138.75mm X 46.75mm X 22.25mm. - Weight 282g- 292g	10.07.2024

R1	R1 4800 - R1-030036		5mm Bullets - 36.5wh	95.60mm X 46.75mm X 20mm - Weight 162g-172g	10.07.2024
Team EAM	EAM 130C GRAPH-X EAM42130-2		5mm Bullets - 31.08wh	94.65mm x 46.95mm x 18.7mm - Weight 162g-172g	10.07.2024
Team EAM	EAM 130C GRAPH-X EAM84130-2		5mm Bullets - 62.16wh	139mm x 47mm x 25mm - Weight 315g-325g	10.07.2024
Team EAM	EAM 140C GRAPH-X EAM63140-2		5mm Bullets - 46.62wh	139mm x 47mm x 23.25mm - Weight 280g-290g	10.07.2024
Team EAM	EAM 160C GRAPH-X EAM50160-2		5mm Bullets - 37wh	138.85mm x 46.75mm x 18.20mm - Weight 222g-232g	10.07.2024
Team Exalt	EXALT X-RATED 135C EXA3203		5mm Bullets - 39.52wh	96.20mm x 47mm x 20.80mm - Weight 180g-190g	10.07.2024
Team Exalt	EXALT X-RATED 150C EXA3206		5mm Bullets - 45.88wh	139mm x 47mm x 22.40mm - Weight 281g-291g	10.07.2024
Team Exalt	EXALT X-RATED 135C EXA3207		5mm Bullets - 60.68wh	138.20mm x 46.85mm x 24.80mm - Weight 314g-324g	10.07.2024
Team Exalt	EXALT X-RATED 150C EXA3201		5mm Bullets - 32.56wh	96.55mm x 47.45mm x 25mm - Weight 211g-221g	10.07.2024
Team Exalt	EXALT X-RATED 135C EXA3202		5mm Bullets - 42.18wh	96.25mm x 47mm x 25mm - Weight 218g-228g	10.07.2024
PROTEK RC	Protek LiHV 130C PTK-5115-22		5mm Bullets - 47.9wh	138.25mm X 46.25mm X 22.25mm - Weight 270g-280	10.07.2024
PROTEK RC	Protek LiHV 130C PTK-5128-22		5mm Bullets - 51.7wh	138.45mm X 46.65mm X 22.15mm - Weight 285g-295g	10.07.2024
PROTEK RC	Protek LiHV 130C PTK-5127-22		5mm Bullets - 56.2wh	137.85mm X 47.00mm X 25.00mm - Weight 300g-310g	10.07.2024
TEKIN	TEKIN Titanium 160C TT1656		5mm Bullets - 45.88wh	139mm X 46.75mm X 22.5mm - Weight 285g-295g	10.07.2024

TEKIN	Tekin Titanium 140C TT1657		5mm Bullets - 43.66wh	139mm X 47.00mm X 20.00mm Weight 240g- 250g	10.07.2024
TEKIN	Tekin Titanium 140C TT1653		5mm Bullets - 41.44wh	96.25mm X 47mm X 25mm Weight 220g-230g	10.07.2024
TEKIN	TEKIN Titanium 160C TT1652		5mm Bullets - 32.56wh	95.9mm X 47mm X 25mm Weight 210g- 220g	10.07.2024
SUNPADOW	Sunpadow 140C/70C JR0040H		5mm Bullets - 34.96wh	95.75mm X 47.00mm X 20.2mm. Weight 168g-178g	10.07.2024
SUNPADOW	Sunpadow 140C/70C JR0022H		5mm Bullets - 74.48wh	138.35mm X 46.9mm X 25.00mm Weight 320g-330g	10.07.2024
LRP	LRP Graphene 135C 432277		5mm Bullets - 38.7wh	138mm x 46.4mm x 19.8mm Weight 240g-250g	13.07.2024
LRP	LRP Graphene 135C 431281		5mm Bullets - 46.3wh	138.3mm x 46.65mm x 22.75mm Weight 270g-280g	13.07.2024
LRP	LRP Graphene 135C 431279		5mm Bullets - 71.4wh	138.5mm x 46.9mm x 25mm Weight 325g-335g	13.07.2024
LRP	LRP Graphene 135C 431276		5mm Bullets - 56.2wh	138.4mm x 47.00mm x 25.1mm Weight 295g-305g	13.07.2024
LRP	LRP Graphene 120C 432282		5mm Bullets - 49.4wh	138.5mm x 46.8mm x 19.8mm Weight 240g-250g	13.07.2024
LRP	LRP Graphene 135C 431280		5mm Bullets - 61.5wh	138.25mm x 46.75mm x 25.00mm Weight 328g-338g	13.07.2024
LRP	LRP Graphene 135C 431272		5mm Bullets - 39.5wh	138.25mm x 46.65mm x 17.5mm Weight 228g-238g	13.07.2024
LRP	LRP Graphene 120C 431286		5mm Bullets - 34.9wh	96.35mm x 46.5mm x 22.25mm Weight 180g-190g	13.07.2024
NOSRAM	NOSRAM Graphene 120C 999660		5mm Bullets - 34.9wh	96.35mm x 46.4mm x 22.25mm Weight 180g-190g	13.07.2024

NOSRAM	NOSRAM Graphene 135C 999746		5mm Bullets - 38.7wh	138mm x 46.45mm x 20.00mm Weight 240g-245g	13.07.2024
NOSRAM	NOSRAM Graphene 135C 999656		5mm Bullets - 61.5wh	138.25mm x 47.00mm x 25.00mm Weight 325g-335g	13.07.2024
NOSRAM	NOSRAM Graphene 135C 999654		5mm Bullets - 71.4wh	138.5mm x 46.75mm x 25mm Weight 325g-335g	13.07.2024
NOSRAM	NOSRAM Graphene 135C 999655		5mm Bullets - 46.4wh	138.4mm x 46.75mm x 22.5mm Weight 265g-275g	13.07.2024
NOSRAM	NOSRAM Graphene 120C 999758		5mm Bullets - 49.4wh	138mm x 46.5mm x 19.8mm Weight 235g-245g	13.07.2024
NOSRAM	NOSRAM Graphene 135C 999652		5mm Bullets - 56.2wh	138.5mm x 46.8mm x 25mm Weight 300g-310g	13.07.2024
CAYOTE	CAYOTE 145C CA702S145		5mm Bullets - 53.2wh	138mm x 46.75mm x 22.00mm Weight 265g-275g	13.07.2024
CAYOTE	CAYOTE 145C CA922S145		5mm Bullets - 69.92wh	138.35mm x 46.2mm x 25.00mm Weight 325g-335g	13.07.2024
CAYOTE	CAYOTE 145C CA532S145		5mm Bullets - 40.28wh	138.5mm x 46.5mm x 16.2mm Weight 205g-215g	13.07.2024
CAYOTE	CAYOTE 145C CA682S145		5mm Bullets - 51.68wh	138.35mm x 46.5mm x 20.00mm Weight 235g-245g	13.07.2024
CAYOTE	CAYOTE 145C CA632S145		5mm Bullets - 47.88wh	138.25mm x 46.25mm x 18.3mm Weight 225g-235g	13.07.2024
CAYOTE	CAYOTE 145C CA652S145		5mm Bullets - 49.4wh	95.5mm x 46.5mm x 24.85mm Weight 225g-235g	13.07.2024
CAYOTE	CAYOTE 145C CA552S145		5mm Bullets - 41.8wh	95.75mm x 46.75mm x 22.3mm Weight 205g-215g	13.07.2024
CAYOTE	CAYOTE 145C CA392S145		5mm Bullets - 29.64wh	95.65mm x 46.65mm x 15.85mm Weight 125g-135g	13.07.2024










CAYOTE	CAYOTE 145C CA502S145		5mm Bullets - 38.00wh	95.6mm x 46.7mm x 19.75mm Weight 165g-175g	13.07.2024
CAYOTE	CAYOTE 145C CA462S145		5mm Bullets - 34.96wh	96.0mm x 46.75mm x 18.5mm Weight 160g-170g	13.07.2024

BATTERIES ON THIS HOMOLOGATION LIST HAVE BEEN CERTIFIED FOR COMPLIANCE WITH UN38.3, TESTS T1-T8.

Submitted by:	Label Details, Part #	Illustration only	Manufacturer Supplied Data.	IFMAR measured Specification,	Approval Date
---------------	-----------------------	-------------------	-----------------------------	-------------------------------	---------------

BATTERIES BELOW THIS LEVEL WERE PREVIOUSLY APPROVED BY IFMAR FOR 2024 WORLD CHAMPIONSHIP EVENTS.




2S LiPo STICK BATTERIES

Associated Electrics	Reedy Zappers SG5 # 27396		Reedy LiPo 2S 7.6v. 36.48 Wh. 90C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 158/172 g.	11.03.23
Associated Electrics	Reedy Zappers SG5 # 27382		Reedy LiPo 2S 7.6v. 49.0 Wh. 90C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 216/234 g.	11.03.23
Kiel Technology	Fyrwork ECP plus # F45200-2S2P		Kiel LiPo 2S 7.4v. 33.3 Wh. 200C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 206/224 g.	11.03.23
Kiel Technology	Fyrwork ECP plus # F60130-2S2P		Kiel LiPo 2S 7.4v. 44.4 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 213/231 g.	11.03.23
Kiel Technology	Fyrwork ECP plus # F63130-2S2P HV		Kiel LiPo 2S 7.6v. 47.8 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 210/228 g.	11.03.23
Kiel Technology	Fyrwork ECP plus # F82130-2S2P		Kiel LiPo 2S 7.4v. 60.6 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 306/332 g.	11.03.23
Kiel Technology	Fyrwork ECP plus # F90130-2S2P HV		Kiel LiPo 2S 7.6v. 68.4 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 305/331 g.	11.03.23
LRP	LRP G4.1 LCG Stock Spec # 432287		LRP LiPo 2S 7.6v. 28.1 Wh. 135C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 149/161 g.	11.03.23
LRP	LRP G4.1 LCG Modified # 432273		LRP LiPo 2S 7.6v. 31.9 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 154/166 g.	11.03.23

LRP	LRP G4.1 HV Stock Spec. # 432285		LRP LiPo 2S 7.6v. 47.1 Wh. 135C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 216/234 g.	11.03.23
Nosram	Nosram G4.1 HV Stock Spec. # 999743		Nosram LiPo 2S 7.6v. 28.1 Wh. 135C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 149/161 g.	11.03.23
Nosram	Nosram G4.1 Modified # 999753		Nosram LiPo 2S 7.6v. 31.9 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 154/166 g.	11.03.23
Nosram	Nosram G4.1 HV Stock Spec. # 999759		Nosram LiPo 2S 7.6v. 47.1 Wh. 135C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 215/233 g.	11.03.23
ProTek RC	ProTek RC # PTK-5117-22		ProTek LiPo 2S 7.6v. 36.5 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 158/172 g.	11.03.23
ProTek RC	ProTek RC # PTK-5102-22		ProTek LiPo 2S 7.6v. 38.0 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 197/213 g.	11.03.23
ProTek RC	ProTek RC # PTK-5114-22		ProTek LiPo 2S 7.6v. 48.6 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 211/229 g.	11.03.23
Ruddog Dist.	Ruddog # RP-0678		Ruddog LiPo 2S 7.6v. 34.4 Wh. 150C Max charge rate: 2C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 153/165 g.	11.03.23

BATTERIES BELOW THIS LEVEL WERE APPROVED BY IFMAR FOR 2022 AND ARE ALLOWED AT 2024 EVENTS.

2S LiPo STICK BATTERIES

Associated Electrics	Reedy Zappers SG5 # 27381		Reedy LiPo 2S 7.6v. 46.0 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 235/255 g.	27.04.22
Associated Electrics	Reedy Zappers SG5 # 27380		Reedy LiPo 2S 7.6v. 52.0 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 274/296 g.	27.04.22
Freemax Technology	Arrowmax # AM 700205		Freemax Tech LiPo 2S 7.4v. 42.9 Wh. 130C Max charge rate: 1C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 212/230 g.	27.04.22
Freemax Technology	Arrowmax # AM 700106		Freemax Tech. LiPo 2S 7.4v. 60.7 Wh. 130C Max charge rate: 1C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 314/340 g.	27.04.22








Intellect Pioneering Battery Technology	IP Platinum Series # BG2S4800PT2		Intellect LiPo 2S 7.6v. 36.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 158/172 g.	27.04.22
Intellect Pioneering Battery Technology	IP Platinum Series # CC2S5900PT2		Intellect LiPo 2S 7.6v. 45.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 235/255 g.	27.04.22
Intellect Pioneering Battery Technology	IP Platinum Series # BG2S6400PT2		Intellect LiPo 2S 7.6v. 49.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 211/229 g.	27.04.22
Intellect Pioneering Battery Technology	IP Platinum Series # CC2S7000PT2		Intellect LiPo 2S 7.6v. 53.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 274/296 g.	27.04.22
Italtrading	EZ-Power # EZP6100/2		Ital LiPo 2S 7.6v. 46.4 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 235/255 g.	27.04.22
Italtrading	EZ-Power # EZP6800/2		Ital LiPo 2S 7.6v. 51.7 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 274/296 g.	27.04.22
LRP	LRP G4.1 HV LCG Modified # 432282		LRP LiPo 2S 7.6v. 44.8 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 241/261 g.	27.04.22
LRP	LRP G4 Modified # 431271		LRP LiPo 2S 7.6v. 50.9 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 263/285 g.	27.04.22
Nosram	Nosram G4.1 HV Stock Spec. # 999747		Nosram LiPo 2S 7.6v. 41.8 Wh. 135C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 229/249 g.	27.04.22
Nosram	Nosram G4.1 HV LCG Modified # 999758		Nosram LiPo 2S 7.6v. 44.8 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 239/259 g.	27.04.22
Nosram	Nosram G4 Modified # 999657		Nosram LiPo 2S 7.6v. 50.9 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 263/285 g.	27.04.22
Premium RC	Corsatec # CT10001		Corsatec LiPo 2S 7.6v. 48.6 Wh. 138C Max charge rate: 2C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 210/228 g.	27.04.22
Premium RC	Corsatec # CT10012		Corsatec LiPo 2S 7.6v. 56.2 Wh. 138C Max charge rate: 2C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 258/280 g.	27.04.22






Premium RC	Corsatec # CT10011		Corsatec LiPo 2S 7.6v. 63.8 Wh. 138C Max charge rate: 2C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 288/312 g.	27.04.22
Shenzhen Grepow	GensAce Redline # GEA4000 2S13D4		GensAce LiPo 2S 7.6v. 30.4 Wh. 130C Max charge rate: 1C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 135/147 g.	27.04.22
Shenzhen Grepow	GensAce Redline # GEA5100 2S13D5		GensAce LiPo 2S 7.6v. 38.8 Wh. 130C Max charge rate: 1C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 191/207 g.	27.04.22
Shenzhen Grepow	GensAce Redline # GEA6000 2S13D5		GensAce LiPo 2S 7.6v. 45.6 Wh. 130C Max charge rate: 1C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 210/228 g.	27.04.22
United Sino Enterprises	ORCA Infinite X # LP21IN243TS		United Sino Ent. LiPo 2S 7.4v. 31.8 Wh. 135C Max charge rate: 1C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 156/168 g.	27.04.22
United Sino Enterprises	ORCA Infinite X # LP21B2S61SL		United Sino Ent. LiPo 2S 7.4v. 45.0 Wh. 135C Max charge rate: 1C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 234/254 g.	27.04.22
United Sino Enterprises	ORCA Infinite X # LP21BL2S64T		United Sino Ent. LiPo 2S 7.4v. 47.3 Wh. 135C Max charge rate: 1C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 278/302 g.	27.04.22
United Sino Enterprises	ORCA Infinite X # LP21BL2S86T		United Sino Ent. LiPo 2S 7.4v. 63.6 Wh. 135C Max charge rate: 1C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 308/334 g.	27.04.22
Xiamen 3-Circles	Sunpadow Platin # JA0031		3-Circles LiPo 2S 7.4v. 29.6 Wh. 130C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 154/166 g.	27.04.22
Xiamen 3-Circles	Sunpadow Platin # JA0018		3-Circles LiPo 2S 7.4v. 40.0 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 214/232 g.	27.04.22
Xiamen 3-Circles	Sunpadow Platin # JA0021		3-Circles LiPo 2S 7.4v. 40.7 Wh. 130C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 241/261 g.	27.04.22
Xiamen 3-Circles	Sunpadow Platin # JA0025H		3-Circles LiPo 2S 7.6v. 49.4 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 247/267 g.	27.04.22
Xiamen 3-Circles	Sunpadow Platin # JA0032		3-Circles LiPo 2S 7.4v. 59.2 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 306/332 g.	27.04.22

BATTERIES BELOW THIS LEVEL WERE APPROVED BY IFMAR FOR 2020 AND ARE ALLOWED AT 2024 EVENTS.

2S LIPo STICK BATTERIES








Associated Electrics	Reedy Zappers # 27345		Reedy LiPo 2S 7.6v. 46.0 Wh. 115C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 264/286 g.	01.01.20
Freemax Technology	Arrowmax # AM 700715		Freemax Tech. LiPo 2S 7.4v. 43.7 Wh. 120C Max charge rate: 1C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 238/258 g.	01.01.20
Freemax Technology	Arrowmax # AM 700710		Freemax Tech. LiPo 2S 7.4v. 44.4 Wh. 120C Max charge rate: 1C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 258/280 g.	01.01.20
Modern Creations	T/Silverback Spiral-G # G5800 1402SIND		Modern Creations LiPo 2S 7.4v. 42.9 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 238/258 g.	01.01.20
Muchmore Racing	Impact # MLSG- SLCG5800		Muchmore LiPo 2S 7.4v. 43.0 Wh. 130C Max charge rate: 1C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 230/250 g.	01.01.20
Neidhart SA	Absima # 4150009		Neidhart SA LiPo 2S 7.6v. 33.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 171/185 g.	01.01.20
Neidhart SA	Absima # 4150007		Neidhart SA LiPo 2S 7.6v. 44.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 256/278 g.	01.01.20
Neidhart SA	Absima # 4150008		Neidhart SA LiPo 2S 7.6v. 46.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 209/227 g.	01.01.20
Neidhart SA	Absima # 4150006		Neidhart SA LiPo 2S 7.6v. 63.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 300/324 g.	01.01.20
Neidhart SA	Orion V-Max # ORI 14522		Neidhart SA LiPo 2S 7.6v. 28.9 Wh. 128C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 138/150 g.	01.01.20
Neidhart SA	Orion V-Max # ORI 14523		Neidhart SA LiPo 2S 7.6v. 31.9 Wh. 128C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 170/184 g.	01.01.20
Neidhart SA	Orion V-Max # ORI 14524		Neidhart SA LiPo 2S 7.6v. 47.1 Wh. 128C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 202/218 g.	01.01.20

Neidhart SA	Orion V-Max # ORI 14525		Neidhart SA LiPo 2S 7.6v. 54.7 Wh. 128C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 265/287 g.	01.01.20
Neidhart SA	Orion V-Max # ORI 14526		Neidhart SA LiPo 2S 7.6v. 62.3 Wh. 128C Max charge rate: 3C 4 x 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 307/333 g.	01.01.20
Neidhart SA	Performa # PA9374		Neidhart SA LiPo 2S 7.6v. 33.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 170/184 g.	01.01.20
Neidhart SA	Performa # PA9373		Neidhart SA LiPo 2S 7.6v. 47.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 264/286 g.	01.01.20
Neidhart SA	Performa # PA9372		Neidhart SA LiPo 2S 7.6v. 63.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 281/305 g.	01.01.20
Shenzhen Grepow	GensAce Redline # 130C40002S1P HC61-HV		GensAce LiPo 2S 7.6v. 30.4 Wh. 130C Max charge rate: 1C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 120/130 g.	01.01.20
Shenzhen Grepow	GensAce Redline # 130C51002S2P HC65-HV		GensAce LiPo 2S 7.6v. 38.8 Wh. 130C Max charge rate: 1C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 204/220 g.	01.01.20
Shenzhen Grepow	GensAce Redline # 130C58002S1P HC56-HV		GensAce LiPo 2S 7.6v. 44.1 Wh. 130C Max charge rate: 1C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 216/234 g.	01.01.20
Shenzhen Grepow	GensAce Redline # 130C60002S2P HC57-HV		GensAce LiPo 2S 7.6v. 45.6 Wh. 130C Max charge rate: 1C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 264/286 g.	01.01.20
Shenzhen Grepow	GensAce Redline # 130C66002S1P HC57-HV		GensAce LiPo 2S 7.6v. 50.2 Wh. 130C Max charge rate: 1C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 269/291 g.	01.01.20
Shenzhen Grepow	GensAce Redline # 130C82002S1P HC58-HV		GensAce LiPo 2S 7.6v. 62.3 Wh. 130C Max charge rate: 1C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 286/310 g.	01.01.20
United Sino Enterprises	ORCA Infinite X # LP19IN2S60T		United Sino Ent. LiPo 2S 7.4v. 44.4 Wh. 130C Max charge rate: 1C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 239/259 g.	01.01.20
United Sino Enterprises	ORCA Infinite X # LP19IN2S65T		United Sino Ent. LiPo 2S 7.4v. 48.1 Wh. 130C Max charge rate: 1C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 259/281 g.	01.01.20

Xiamen 3-Circles	Sunpadow Platin # JA0006		3-Circles LiPo 2S 7.4v. 31.1 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 182/198 g.	01.01.20
Xiamen 3-Circles	Sunpadow Platin # JA0004		3-Circles LiPo 2S 7.4v. 38.5 Wh. 110C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 202/218 g.	01.01.20
Xiamen 3-Circles	Sunpadow Platin # JD0002		3-Circles LiPo 2S 7.4v. 38.5 Wh. 130C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 235/255 g.	01.01.20
Xiamen 3-Circles	Sunpadow Platin # JA0001		3-Circles LiPo 2S 7.4v. 44.4 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 270/292 g.	01.01.20
Xiamen 3-Circles	Sunpadow Platin # JA0003		3-Circles LiPo 2S 7.4v. 60.7 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 304/330 g.	01.01.20






BATTERIES BELOW THIS LEVEL WERE APPROVED BY IFMAR FOR 2019 AND ARE ALLOWED AT 2024 EVENTS.

2S LiPo STICK BATTERIES

Associated Electrics	Reedy Zappers # 27338		Reedy LiPo 2S 7.6v. 32.0 Wh. 80C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 149/161 g.	28.02.19
Associated Electrics	Reedy Zappers # 27336 (Was # 27323)		Reedy LiPo 2S 7.6v. 45.0 Wh. 80C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 207/225 g.	28.02.19
Intellect Battery	IP # BG2S5000HV4		Intellect LiPo 2S 7.6v. 38.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 197/213 g.	28.02.19
Intellect Battery	IP # BG2S6000HV4		Intellect LiPo 2S 7.6v. 46.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 207/225 g.	28.02.19
Intellect Battery	IP # CC2S6000HV4		Intellect LiPo 2S 7.6v. 46.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 259/281 g.	28.02.19
Intellect Battery	IP # CC2S7000HV4		Intellect LiPo 2S 7.6v. 53.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 259/281 g.	28.02.19
Intellect Battery	IP # CC2S7600HV4		Intellect LiPo 2S 7.6v. 58.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 293/317 g.	28.02.19

Intellect Battery	IP # CC2S8400HV4		Intellect LiPo 2S 7.6v. 64.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 317/343 g.	28.02.19
LRP	LRP G3 Modified # 430273		LRP LiPo 2S 7.6v. 29.6 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 149/161 g.	28.02.19
LRP	LRP G3 Modified # 430286		LRP LiPo 2S 7.6v. 34.2 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 175/189 g.	28.02.19
LRP	LRP G3 Stock spec # 430285		LRP LiPo 2S 7.6v. 44.1 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 211/229 g.	28.02.19
Muchmore Racing	Impact # MLSG-STLCGHV3800		Muchmore LiPo 2S 7.6v. 28.9 Wh. 130C Max charge rate: 1C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 181/197 g.	28.02.19
Nosram	Nosram G3 Modified # 999553		Nosram LiPo 2S 7.6v. 29.6 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 149/161 g.	28.02.19
Nosram	Nosram G3 Modified # 999560		Nosram LiPo 2S 7.6v. 34.2 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 175/189 g.	28.02.19
Nosram	Nosram G3 Stock Spec # 999559		Nosram LiPo 2S 7.6v. 44.1 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 211/229 g.	28.02.19
Neidhart SA	Performa # PA9304		Neidhart SA LiPo 2S 7.4v. 27.0 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 124/134 g.	28.02.19
Neidhart SA	Performa # PA9305		Neidhart SA LiPo 2S 7.6v. 30.0 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 126/136 g.	28.02.19
Neidhart SA	Performa # PA9306		Neidhart SA LiPo 2S 7.4v. 43.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 202/218 g.	28.02.19
Neidhart SA	Performa # PA9307		Neidhart SA LiPo 2S 7.6v. 46.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 204/222 g.	28.02.19
Process Measurement & Analysis	Optipower # OPR 28002S100B		Optipower LiPo 2S 7.4v. 20.7 Wh. 100C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 124/134 g.	28.02.19

Process Measurement & Analysis	Optipower # OPR 33002S100B		Optipower LiPo 2S 7.4v. 24.4 Wh. 100C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 141/153 g.	28.02.19
Process Measurement & Analysis	Optipower # OPR 40002S-B		Optipower LiPo 2S 7.4v. 28.8 Wh. 60C Max charge rate: 2C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 197/213 g.	28.02.19
ProTek RC	ProTek RC # PTK-5100-19		ProTek LiPo 2S 7.6v. 27.4 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 149/161 g.	28.02.19
ProTek RC	ProTek RC # PTK-5124-19		ProTek LiPo 2S 7.6v. 31.1 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 149/161 g.	28.02.19
ProTek RC	ProTek RC # PTK-5102-19		ProTek LiPo 2S 7.6v. 37.2 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 195/211 g.	28.02.19
ProTek RC	ProTek RC # PTK-5114-19		ProTek LiPo 2S 7.6v. 44.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 207/225 g.	28.02.19
RC Concept	Omega # 50C5135000T		RC Concept LiPo 2S 7.6v. 26.6 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 134/146 g.	28.02.19
RC Concept	Omega # 50C5145000T		RC Concept LiPo 2S 7.4v. 33.3 Wh. 100C Max charge rate: 3C 4 mm. Tubes.	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 194/210 g.	28.02.19
RC Concept	Omega # 50C514800000		RC Concept LiPo 2S 7.6v. 36.5 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 197/213 g.	28.02.19
Team Corally	Corally Voltax HV # 49606		Corally LiPo 2S 7.6v. 45.6 Wh. 120C Max charge rate: 2C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 206/224 g.	28.02.19
Xiamen 3-Circles	Sunpadow # S638066		3-Circles LiPo 2S 7.4v. 28.1 Wh. 130C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 157/170 g.	28.02.19
Xiamen 3-Circles	Sunpadow # 7150135		3-Circles LiPo 2S 7.4v. 33.3 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 212/230 g.	28.02.19
Xiamen 3-Circles	Sunpadow # S653065		3-Circles LiPo 2S 7.4v. 39.2 Wh. 130C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 243/263 g.	28.02.19

Xiamen 3-Circles	Sunpadow # S684064		3-Circles LiPo 2S 7.4v. 62.2 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 325/353 g.	28.02.19
Yokomo	Yokomo # YB-V235B		Yokomo LiPo 2S 7.4v. 25.9 Wh. 100C Max charge rate: 2C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 151/163 g.	28.02.19
Yokomo	Yokomo # YB-V246B		Yokomo LiPo 2S 7.4v. 34.0 Wh. 100C Max charge rate: 2C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 205/223 g.	28.02.19
Yokomo	Yokomo # RPB-55LCG		Yokomo LiPo 2S 7.6v. 41.8 Wh. 140C Max charge rate: 2C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 232/252 g.	28.02.19
Yokomo	Yokomo # RPB-60LCG		Yokomo LiPo 2S 7.4v. 44.4 Wh. 140C Max charge rate: 2C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - 277/301 g.	28.02.19

